



Durchmesser Toleranz	Länge mm	Leistung Watt bei 230 Volt							
6.5 mm -0.01 -0.03	40	100	125	160	175	200			
	50	100	125	160	200	250			
	60	125	160	200	250	315			
	80	125	160	180	200	250	280	315	350
	100	100	160	200	250	315	350	400	
	x x	130 160	220 350	350 400					
8 mm -0.01 -0.03	40	100	160	200	250				
	50	125	160	200	250	315			
	60	100	125	140	160	200	250	280	315
	80	160	200	250	315	400	500		
	100	200	250	280	315	400			
	x x	130 160	250 200	315 400	400				
10 mm -0.02 -0.04	40	100	125	200	250	315			
	50	100	160	200	250	315	400		
	60	125	160	200	250	315	400	500	
	80	160	200	250	315	400	500	630	
	100	160	200	250	315	400	500	560	630
	x x	130 160 200 250	315 400 400 630	400 630 630	500 630 800	630 800	800		
12.5 mm -0.02 -0.04	40	100	160	200	250	315	400		
	50	100	125	160	200	250	315	400	500
	60	125	160	200	250	315	400	500	
	80	200	250	315	400	500	630	800	
	100	250	315	400	500	630	800	1000	
	x x	130 160 180 200 250 300	400 500 800 630 800 600	500 630 1000 800 900 1500	630 800 1000 1000 1500	800 1000 1250	1000		
16 mm -0.02 -0.04	40	100	160	200	250	315	400	500	
	50	160	200	250	315	400	500	630	
	60	160	200	250	315	400	500	630	
	80	250	315	400	500	630	800	1000	
	100	315	400	500	630	800	1000	1250	
	x x	130 160 180 200 250 300	500 630 1000 800 1000 1250	630 800 1000 1250 1600	800 1000 1250 1600 2000	1000 1250 1800	1400		
20 mm -0.03 -0.05	x	50	200	250	315	400			
	x	60	200	315	500	630	800		
		80	400	500	630	800	1000	1250	
		100	400	630	800	1000	1250	1600	
		130	630	800	1000	1250	1600	2000	
		160	1000	1250	1600	2000	2500		
	200	1250	1600	2000	2500	3150			
	250	1600	2000	2500	3150				
	300	2000	2500	3150	4000				

Sonderanfertigungen
 sind jederzeit möglich,
 fragen Sie uns bitte an.

Die aufgeführten Typen sind **sofort ab Lager lieferbar**, ausser die mit **x** gekennzeichneten Typen haben ca. 1 Woche Lieferfrist. **Andere Ausführungen mit Flansch etc. auf Anfrage.**